

Amendments to the Claims

The listing of claims will replace all prior versions, and listings of claims in the application.

1. *(Previously Presented)* A cable modem termination system (CMTS) that can receive signal bursts transmitted on an upstream channel of a cable modem system, the CMTS comprising:

 a demodulator for receiving the signal bursts on the upstream channel;

 a media access controller (MAC) that generates for downstream transmission MAP messages that assign time slots in which cable modems may transmit signal bursts on the upstream channel, the MAP messages including idle slots that are assigned to no cable modems;

 a transmitter that transmits the MAP messages with the idle slots downstream to the cable modems; and

 an adaptive notch filter connected to the demodulator, wherein coefficients of the adaptive notch filter are adjusted to suppress noise on the upstream channel sensed during the idle slots.

2. *(Canceled)*

3. *(Previously Presented)* The CMTS of claim 1, additionally comprising a decision feedback equalizer coupled to the demodulator and the notch filter, the decision

feedback equalizer having a feedback filter using the adjusted coefficients of the adaptive notch filter to compensate for its distortion introduced by the adaptive notch filter.

4. (*Original*) The CMTS of claim 3, in which the decision feedback equalizer has a feedforward filter for establishing pre-equalization coefficients.

5. (*Original*) The CMTS of claim 4, in which the demodulator converts the signal bursts to binary data, the system additionally comprising a signal path for carrying the binary data from the demodulator to the MAC, the notch filter and the decision feedback equalizer being in the signal path.

6. (*Original*) The CMTS of claim 5, in which the signal path carries both the binary data and pre-equalization coefficients to the MAC in band such that the coefficients are appended to the binary data.

7. (*Original*) The CMTS of claim 6, in which the pre-equalization coefficients do not reflect noise received by the demodulator, the system additionally comprising an upstream transmitter for transmitting the pre-equalization coefficients established by the feedforward filter.

8. (*Original*) The CMTS of claim 7, in which the upstream transmitter is connected to the MAC to transmit the pre-equalization coefficients established by the feed forward filter.

9. *(Original)* A cable modem termination system (CMTS) that can receive a signal transmitted in a cable modem system on an upstream channel, the CMTS comprising:
- a demodulator;
 - a notch filter connected to the demodulator, the notch filter having coefficients that are adjustable to cancel noise applied to the demodulator;
 - a media access controller (MAC) that processes binary data and generates for downstream transmission MAP messages that assign time slots in which cable modems may transmit signal bursts on the upstream channel; and
 - a decision feedback equalizer coupled to the demodulator, the decision feedback equalizer including a feedforward filter for establishing pre-equalization coefficients.
10. *(Original)* The CMTS of claim 9, in which both binary data and pre-equalization coefficients are provided to the MAC in band such that the coefficients are appended to the binary data.
11. *(Original)* The CMTS of claim 10, in which the pre-equalization coefficients do not reflect noise applied to the demodulator, the system additionally comprising an upstream transmitter connected to the MAC to transmit the pre-equalization coefficients established by the feedforward filter.

12. (*Currently Amended*) A method for compensating for conditions on an upstream channel from a plurality of cable modems to a cable modem termination system (CMTS), the method comprising the steps of:

transmitting on a downstream channel from the CMTS to a plurality of cable modems MAP messages that assign time slots in which cable modems may transmit signal bursts on the upstream channel, the MAP messages including idle slots that are assigned to no cable modems;

monitoring conditions on the upstream channel during the idle slots; ~~and~~
compensating for the monitored conditions on the upstream channel; and
receiving at the CMTS signal bursts on the upstream channel after such compensation.

13. (*Original*) The method of claim 12, in which the monitoring step comprises sensing the noise on the upstream channel during the idle slots.

14. (*Original*) The method of claim 13, in which the compensating step comprises adjusting the coefficients of a notch filter to compensate for the sensed noise on the upstream channel during the idle slots.

15. (*Original*) The method of claim 14, in which the compensating step further comprises adjusting a feedback filter of a decision feedback filter in series with the notch filter to have the same coefficients as the notch filter to compensate for its distortion.

16. (*Original*) The method of claim 15, additionally comprising the steps of:

 receiving on the upstream channel a ranging signal from a cable modem;

 adjusting coefficients of a feedforward filter of the decision feedback filter
responsive to the received ranging signal to compensate for intersymbol interference on
the upstream channel; and

 transmitting the adjusted coefficients on a downstream channel to the cable
modem for the purpose of pre-equalization.

17. (*Original*) The method of claim 16, in which the transmitting steps transmit the
MAP messages and the adjusted coefficients on the same channel.

18. (*Original*) A method for compensating for conditions on an upstream channel
from a plurality of cable modems to a cable modem termination system (CMTS), the
method comprising the steps of:

 compensating for noise on an upstream channel;

 receiving on the compensated upstream channel a ranging signal from one of the
cable modems;

 adjusting filter coefficients to compensate for intersymbol interference on the
upstream channel responsive to the received ranging signal; and

 transmitting the adjusted coefficients on a downstream channel to the cable
modem for the purpose of pre-equalization of the upstream channel.

19. *(Original)* The method of claim 18, in which the adjusting step comprises adjusting coefficients of a feedforward filter of a decision feedback filter.
20. *(Original)* The method of claim 19, in which the compensating step comprises adjusting the coefficients of a notch filter in series with the decision feedback filter.
21. *(Original)* The method of claim 20, in which the compensating step further comprises adjusting a feedback filter of the decision feedback filter to have the same coefficients as the notch filter to compensate for its distortion.
22. *(Original)* The method of claim 21, additionally comprising the step of transmitting on a downstream channel from the CMTS to the cable modems MAP messages that assign time slots in which cable modems may transmit signal bursts on the upstream channel.
23. *(Original)* The method of claim 22, in which the transmitting steps transmit the MAP messages and the adjusted coefficients on the same channel.
24. *(Canceled)*